


## HydroPower Washing.







The Friction and Tornado Washers are the perfect combination for continuously cleaning heavily contaminated film and rigid plastics using water and mechanical forces. Common impurities such as

- soil and sludge from agricultural film
- paper labels along with dust from post-industrial film and
- food residues found in post-consumer plastics

can be easily removed.

	FW37-60	SD90-90	FW55-70	SD132-130
Performance rigid Flake Size < 10 mm [kg/h]	2000 – 2500	2000 – 2500	4000 – 5000	4000 – 5000
Performance Film > 20 µm Size < 40 mm [kg/h]	500 – 700	500 – 700	700 – 1200	700 – 1200
Main Motor [kW]	30	55 – 75	45	90 – 110
Basket Diameter approx. [mm]	600	900	700	1300
Scraper Drive [kW]	-	0.55	_	0.75

	FW75-80	SD200-140	FW90-100	SD250-180
Performance rigid Flake Size < 10 mm [kg/h]	5000 – 6000	5000 – 6000	6000 – 8000	6000 – 8000
Performance Film > 20 $\mu$ m Size < 40 mm [kg/h]	1200 – 1800	1200 – 1800	2000 – 2500	2000 – 2500
Main Motor [kW]	75	132 – 160	90	200 – 250
Basket Diameter approx. [mm]	800	1400	1000	1800
Scraper Drive [kW]	_	0.75	_	0.75

The achievable throughput capacity depends on the particle size and material thickness.



Pla.to GmbH Nickrischer Strasse 20 02827 Goerlitz Germany

Phone +49 35822 312735 E-Mail info@plato-technology.de Web www.plato-technology.de