

Truck range



24/7 support



Pallet trucks

MDW Compact pedestrian pallet truck

Lift capacity 1600/1800/2000 kg





MDE Compact pedestrian pallet truck with forklift

Lift capacity 2000 kg **Lift height** 0.735 metres



PLF Compact pedestrian pallet truck with foldable platform

Lift capacity 2000/2500 kg





PLR

Compact pedestrian pallet truck with fixed platform

Lift capacity 2000/2500 kg





PLS

Compact pedestrian pallet truck with fixed platform

Lift capacity 2000/2500 kg





ERGO ALL/XLL Stand-in and sit-on low lifters

Lift capacity 2000/3000 kg



Stackers

PSL Compact pedestrian stacker

Lift capacity 1250 kg Lift height up to 2.1 metres



PS Compact pedestrian stacker

Lift capacity 1250 kg **Lift height** up to 4.2 metres



PSH Compact pedestrian stacker

Lift capacity 1600/2000 kg **Lift height** up to 5.4 metres



PSP Pedestrian stacker

Lift capacity 1250/1600 kg **Lift height** up to 5.4 metres







PSD

Compact pedestrian stacker for double-pallet handling

Lift capacity

1250/1600 kg on the straddles Lift height up to 2.1 metres





PDP 200 Double stacker with platform

Lift capacity 2000 kg Lift height 2.1 metres






ERGO A Stand-in stacker

Lift capacity 1600/2000 kg Lift height up to 6.75 metres



ERGO X Sit-on stacker

Lift capacity 1600/2000 kg Lift heights up to 6.75 metres



Lift capacity 1600 kg Lift height 1.5 metres



Lift capacity 1000 kg Lift height up to 6.75 metres



Order pickers

OLP Low level order picker

Lift capacity 2000/2500 kg Lift height 0.22 metres



OLH Low level order picker with lifting platform

Lift capacity 2000/2500 kg Lift height 0.22 metres



OEP

Low level order picker with Ergolift

Lift capacity 1200 kg Lift height up to 1.2 metres

Li-ION

OEH

Low level order picker with Ergolift and lifting platform

Lift capacity 1200 kg Lift height up to 1.2 metres

Li-ION

OSP

Low level order picker with scissor lift forks

Lift capacity 2000 kg Lift height 0.86 metres

Li-ION

OSH

Low level order picker with scissor lift forks and high-lift platform

Lift capacity 2000 kg Lift height 0.86 metres













EPL 100 Medium level order picker

Lift capacity 1000 kg Lift height up to 1.8 metres



EPM High level order picker

Lift capacity 1000 kg Lift height up to 8.25 metres

EPH High level order picker

Lift capacity 1250 kg Lift height up to 10.5 metres



Tow tractor

OTP Tow tractor

Load capacity 3000/5000 kg





Very narrow aisle reach trucks

TERGO® URS* Swivel reach truck

Lift capacity 1250/1500 kg Lift height up to 10.35 metres

Also Man up VNA options

Lift capacity 1100-2000 kg Lift height up to 17.4 metres



Reach trucks

TERGO® ULS/UND Narrow-chassis reach truck

Lift capacity 1200/1400 kg Lift height up to 8.95 metres



TERGO® UMS Standard-chassis reach truck

Lift capacity 1600/2000 kg Lift height up to 8.95 metres




TERGO® UHD/UHX Heavy duty reach truck

Lift capacity 1600/2000/2500 kg Lift height up to 12.1 metres*



*13+ metres available for UHX



Reach truck with telescopic forks

Lift capacity 2000/2500 kg Lift height up to 12.1 metres







TERGO® UFW Four-way reach truck

Lift capacity 2000/2500 kg Lift height up to 9.7 metres





Electric counterbalance forklift trucks

The TX3/TX4/MX electric counterbalance trucks are silent, easy to drive and efficient. They have top-class ergonomics with a fully adjustable driver compartment. An on-board truck computer offers PIN-code-access and service diagnostics. AC drive motor ensures high class performance and low running costs. The counterbalance truck range comes with a full range of mast systems and an efficient battery changeover system.

TX3 3-wheel counterbalance truck

Lift capacity 1250/1500/1600/1800/2000 kg **Lift height** up to 7 metres







TX4 4-wheel counterbalance truck

Lift capacity 1600/1800/2000 kg Lift height up to 7 metres





MX 4-wheel counterbalance truck

Lift capacity 2500/3000/3500 kg **Lift height** up to 7 metres





MXL

4-wheel counterbalance truck

Lift capacity 4000/4500/5000/5500 kg Lift height up to 7 metres

Li-ION



Diesel/LPG counterbalance forklift trucks

The D/G internal combustion (Diesel/LPG) counterbalance trucks with car-like driveability – featuring advanced safety and efficiency-enhancing technology. The meter panel provides OnBoard Diagnostics for troubleshooting.

DX2

4-wheel IC counterbalance truck

Lift capacity 1500/1750/2000/ 2500/3000/3200/3500 kg, Diesel/LPG Lift height up to 7 metres



GX2

4-wheel IC counterbalance truck

Lift capacity 4000/4500/5000/5500 kg, Diesel/LPG Lift height up to 7 metres



Li-ION

Models marked with this logo are available with energy efficient lithium-ion technology.





- sale and lease back
- fleet rental
- short-term hire
- hourly rental
- hire and purchase
- core lease



- driver training
- risk assessment
- rack inspection



- warehouse
- counterbalance
- special trucks
- battery change



- vehicle & operator management
- one fleet





- preventative
- full service
- genuine spare parts



Logistic Analyser

It's all about the price.

But what price?

Reduce your Total Cost of Operation with UniCarriers

We agree. Price is everything. Or to be more specific: your Total Cost of Operation (TCO). That's why we're so focused on cutting costs and improving your material handling. The truck and its performance play an important role, but this is even more about how we can support you in optimising your warehouse operations to give you the best value for your money. Which – in the long run – is what creates a winner.

© 2021 MLE B.V. (REGISTRATION NO. 33274459). ALL RIGHTS RESERVED.

Mitsubishi Logisnext Europe reserves the right to make any changes without notice concerning colours, equipment or specifications detailed in this brochure, or to discontinue individual models. The colours of vehicles delivered may differ slightly from those in this brochure. The specifications vary for different countries depending on local market conditions. Please consult your local dealer to ensure that the vehicle delivered accords with your expectations. All values are determined based on the standard condition and may vary due to motor and system tolerances, condition of the truck and operational conditions. Some equipment shown on photos is optional.